

# R95 Series

## Disposable Respirators



### R95 OIL & NON-OIL PROTECTION

NIOSH certified under 42CFR84 regulations to have a filter efficiency level of 95% or greater against oil and non-oil based particulate aerosols up to 10x PEL.

### HANGS LOOSE

Exclusive HandyStrap® allows mask to conveniently hang down around the user's neck so it's always ready for use. And during wear the adjustable cloth strap is more comfortable and cooler.

### VENT HOT AIR, STAY COOLER

Exclusive Ventex® valve lets the hot air out faster so breathing resistance is reduced and workers stay cooler.

### DURA-MESH® SHELL LASTS LONGER

The exclusive Dura-Mesh® shell protects the filter media so it stays cleaner looking longer. Plus it resists collapsing, even in heat and humidity so the respirator holds its shape longer. The result is fewer respirators used and lower cost.

### APPLICATIONS

Hot, humid and dusty environments such as welding, soldering and brazing, grinding, sanding, sweeping, bagging, stone quarrying, metal machining, cement, underground mining, polishing, buffing, lime, poultry and textiles. For oil and non-oil based particulates.

### FEATURES

- 100% PVC-Free.
- HandyStrap®, with buckle, allows mask to hang around the user's neck when not in use.
- Ventex® valve lets the hot air out faster so workers breathe easier and stay cooler.
- R95 protection against both oil and non-oil based particulate aerosols.
- Soft foam nose cushion for added comfort and no pressure points.
- Softspun® lining for increased comfort and durability.
- Exclusive Dura-Mesh® shell resists collapsing in heat and humidity.
- Meets heat and flame resistance in accordance with ANSI/ISEA 110-2003 Section 7.11.1.



R95



**MOLDEX**  
Ideas that wear well.™

## USE AGAINST:

1. Oil and non-oil particulate aerosols.
2. For 2840/1R95 only, nuisance levels (less than OSHA Permissible Exposure Limits) of Organic Vapor Odors and/or Ozone.
3. For 2940/1R95 only, nuisance levels (less than OSHA Permissible Exposure Limits) of Acid Gas Irritants.

## DO NOT USE AGAINST:

1. Concentrations of contaminants which are unknown or are immediately dangerous to life or health.
2. Concentrations of particulates which exceed the maximum use concentration or 10 times the OSHA Permissible Exposure Limit, whichever is lower.
3. Gases, vapors, asbestos, paint spray, sandblasting or particulate materials which generate harmful vapors. These respirators are NOT approved for any vapors or gases, so when 2840/1R95 is used against Organic Vapor Odors and/or Ozone or 2940/1R95 is used against Acid Gas Irritants, do not exceed the OSHA Permissible Exposure Limit.
4. Oil-based particulate aerosols for longer than 8 hours after first use.

## RESTRICTIONS

1. This respirator does not supply oxygen and must not be used in atmospheres containing less than 19.5% oxygen.
2. Do not remain in contaminated area if any physical distress occurs, for example breathing difficulty, dizziness or nausea.
3. Leave contaminated area and replace respirator if it is damaged, distorted, a proper fit can not be obtained or breathing becomes difficult.
4. Prior to each use, carefully inspect the entire respirator, including filter media and strap attachment area for tears and damage. Staple or strap attachment perforations do not effect NIOSH approval.
5. Do not alter, modify, or abuse this respirator.
6. Store unused respirators in box in a clean, dry, non-contaminated area.
7. Dispose of respirator according to your employer's policy and local regulations.
8. Where oil mists are present, dispose no later than eight hours after first use.
9. Dispose no later than thirty days after first use.
10. Use respirator before the "use by" expiration date printed on box.
11. If used for welding, wear appropriate eye and face protection.

## TECHNICAL SERVICE HELP LINE

For technical assistance, call Moldex Technical Service Department at 310/837-6500 ext. 512/550 or 800/421-0668 ext. 512/550.


### MOLDEX-METRIC, INC.

10111 W. Jefferson Blvd. Culver City, CA 90232  
 TEL: 800/421-0668 or 310/837-6500 FAX 310/837-9563  
 www.moldex.com e-mail: sales@moldex.com


### CANADIAN CUSTOMER SERVICE

TEL: 310-837-6500, Ext. 517  
 FAX: 310-837-9563

Moldex, Ideas that wear well, HandyStrap, Softspun, Ventex and Dura-Mesh are registered trademarks of Moldex-Metric, Inc. The mesh design is a trademark of Moldex-Metric, Inc. U.S. Patents #D285,374, #D389,239, #D387,015, #5,970,585, #6,047,698, #4,850,347 and #5,149,468 Made in the U.S.A. 9701-759 REV H 10/08



Moldex-Metric, Inc.  
 CULVER CITY, CALIFORNIA, U.S.A.  
 800/421-0668



TC	PROTECTION <sup>1</sup>	RESPIRATOR										CAUTIONS AND LIMITATIONS <sup>2</sup>			
		00	01	02	03	04	05	06	07	08	09		10		
84A-3331	R95	X	X												AB C J M N O P
84A-3321	R95					X	X								AB C J M N O P
84A-3174	R95									X	X				AB C J M N O P

1. Protection

R95-Particulate Filter (95% filter efficiency level) effective against all particulate aerosols; time use restrictions may apply.

2. Cautions and Limitations

A- Not for use in atmospheres containing less than 19.5 percent oxygen.  
 B- Not for use in atmospheres immediately dangerous to life or health.  
 C- Do not exceed maximum use concentrations established by regulatory standards.  
 J- Failure to properly use and maintain this product could result in injury or death.  
 M- All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA, and other applicable regulations.  
 N- Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.  
 O- Refer to User's Instructions, and/or maintenance manuals for information on use and maintenance of these respirators.  
 P- NIOSH does not evaluate respirators as surgical masks.

## PACKAGING

10 Respirators per Box  
 10 Bags per Case

## LIMITED WARRANTY IMPORTANT NOTICE TO PURCHASER

This limited warranty is made in lieu of the warranties of merchantability, fitness for particular purposes and all other warranties, express or implied. There are no other warranties which extend beyond the description on the face hereof. The physical standards and specifications of Moldex will be met by products sold. **Exclusive Remedies:** damages for the breach of this limited warranty are limited to the replacement of such quantity of Moldex products proved to be defectively manufactured. Except as provided above, Moldex shall not be liable or responsible for any loss, damages, or liability, direct, indirect, incidental, special or consequential, arising out of a sale, use or misuse, or the inability to use products by the user.

### ⚠ WARNING TO USER

1. Follow all instructions and warnings on the use of this respirator and wear during all times of exposure. Failure to do so will reduce respirator effectiveness, wearer protection, and may result in sickness or death.
2. Before use, the user must first be trained by the employer in proper respirator use, in accordance with applicable safety and health standards, for the contaminant and exposure level in the assigned work area.
3. The particulates and other contaminants which can be dangerous to your health include those which you cannot see, taste, or smell.
4. This product has not been sold with warnings or use instructions for personnel involved in health care or related situations, where there may be the possibility of contact with disease or biological hazards. If you are considering such uses, first call the Moldex Technical Service Dept., 310/837-6500 ext. 512/550 or 800/421-0668 ext. 512/550.

## DISTRIBUTED BY:



Printed on Recycled Paper

