







# FOOD GRADE DRY SILICONE



## LU<sup>TM</sup>211

- 
NSF® Nonfood Compounds Program Listed H1 Rated (Registration # 145287)
- 
Meets FDA CFR 21
- 
For use in low pressure applications
- 
5% Silicone
- 
Minimum - Maximum operational temperature range: Low -40 °F (-40 °C) • High 450 °F (232 °C)
- 
HMIS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Extra dry formula for surfaces requiring no transfer
- Improves performance of sliding surfaces and sorting chutes
- Will not attract dust, dirt or other contaminants



**PRESERVE. PROTECT. PREVENT.®**

Sprayon® LU<sup>TM</sup>211 Food Grade Dry Silicone is a low-viscosity silicone formula compatible with most surfaces. The ultra-thin film will not attract dust or dirt and will create a barrier to prevent rust & corrosion. Meets FDA regulation described in Title 21 paragraph 178.3570, when no more than 1 ppm is imparted. Effective from -40 °F to +450 °F. Repels water and is non-corrosive to metals. An excellent lubricant on plastic, fiber gears, extruded parts, wood-to-wood sliding applications and on rubber.

# LUBRICANTS

## FOR USE ON

- Food Processing & Handling Equipment
- Slides • Guides
- Knives • Racks
- Slicers • Saws
- Drives • Grinders
- Heat Sealing Equipment
- Mixers • Chutes
- Conveyors • Belts
- Bottling & Canning Equipment

## FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



LU211

## APPLICATION

Shake well before using. For best results use at room temperature 70 °F. Spray in a well ventilated area away from open flame. Apply multiple thin coats allowing solvents to flash in between. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth. Use extension tube for hard to reach areas

## PERFORMANCE

**PLASTIC & RUBBER SAFE:** Yes  
(Always test before using)  
**TEMPERATURE RANGE:**  
HIGH: 450 °F  
LOW: -40 °F  
**LOAD CAPACITY:** Low  
**CORROSION PREVENTION (ASTM D-1743):** Pass

## PACKAGING

**PACKAGING**  
**STOCK #:** S00211000  
**UPC CODE:** 0-75577-00621-2  
**FILL WT.:** 13.25 oz.  
**PER CASE:** 12  
**CARTON DIMENSION**  
L 11.13" x W 8.44" x H 9.94"

## SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

## RESOURCES

**MSDS/EDS/PRODUCT DATA SHEETS:** Sprayon.com  
**CUSTOMER SERVICE:** 800-777-2966  
**TECHNICAL INFORMATION:** 800-251-2486

## PROPERTIES

**APPEARANCE:** Clear  
**BASE:** Silicone  
**FILM TYPE:** Dry  
**ODOR:** Low  
**CONTAINS P.T.F.E:** No  
**PROPELLANT:** Hydrocarbon Blend  
**WT./GAL.:** 5.39  
**SPECIFIC GRAVITY:** 0.65  
**% VOC AEROSOL:** 60  
**V.O.C. COMPLIANT CALIFORNIA:** Yes  
(For use in manufacturing process only)  
**V.O.C. COMPLIANT OTC STATES:** Yes  
**SARA 313:** None  
**HAPS:** None  
**FLAMMABLE:** Yes  
**FLASH POINT:** <0°F  
**HAZARD RATING:** 2, 4, 0  
**SHELF LIFE:** 3 years from date of manufacture

## NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145287



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.



Scan this code with your mobile phone to download the NSF® Registration Letter for this product

© 2012 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.®



**Sprayon® Products**  
101 Prospect Ave. NW  
Cleveland, OH 44115  
Sprayon.com  
800-777-2966

310-PDS-LU211